

PLASTI 635

Wider version of the PLASTI 330, can also use 500mt laminating rolls.

With its rollers heating system both the use of hot and cold films is allowed. Special features are: independent activation of **cooling fans**, mechanically **adjustable film tension** with side clutch, **silicone rollers**, manual adjustment of the roller pressure with a max **opening of 7 mm**. Moreover, the laminator has 2 front warmed rollers with infrared resistors controlled by a micro processing system which allows a better heat distribution that reduce warming up time. Other 2 cold rolls on the exit side improve the quality of lamination thanks to additional pressure. Reels with internal mandrel of mm 25, 57 or 75 can be used.

SPECIFICATIONS

- ✓ **Max working width (mm):** 635
- ✓ **Max working thickness (mm):** 7
- ✓ **Film thickness (µm):** 25-250
- ✓ **Speed (m/min):** 0-1.6
- ✓ **Max temperature:** 170° C
- ✓ Independent lower roller heating system can be switched off in order to allow single side (upper) hot lamination
- ✓ **Rollers diameter:** 55mm
- ✓ Anti-jamming reverse function
- ✓ Control panel with preset function
- ✓ **Roller pressure adjustment:** manual
- ✓ **Power consumption (W):** 1800
- ✓ **Power requirements (V - Hz):** 230 - 50/60
- ✓ **Dimensions (mm):** 970x490x390
- ✓ **Weight (Kg):** 38



Optional stand



Visit our web site: www.mamosrl.com