



| GC 480 | Covering material (gluing only) | Open case size (turning-in) |
|--------|---------------------------------|------------------------------|
| | H: 30 -520 mm | H: 30-480 mm |
| | W: 70- 820 mm | W: 70-800 mm |
| | T: 80-300 gsm | T: 80- 250 gsm, 1-6 mm board |

| GC 760 | Covering material (gluing only) | Open case size (turning-in) |
|--------|---------------------------------|------------------------------|
| | H: 30 -800 mm | H: 30-760 mm |
| | W: 70- 820 mm | W: 70-800 mm |
| | T: 80-300 gsm | T: 80- 250 gsm, 1-6 mm board |

Casemaker

GC480/760

COMPACT is a semiautomatic machine that allows the production of hard covers, photo albums or luxury boxes.

The machine consist of professional hot & cold gluer with high diameter stainless steel rollers, vacuum table, positioning device for multi-piece cases and manual turning-in mechanism. It is designed as entry level machine for small runs.

Can apply glue on flat surfaces like paper, eco leather, pvc. It requires little space for installation.



Fully designed & made in Europe

KEY FEATURES

- cold & hot glue ready
- stainless steel rollers (acid resistant), big diameter for better application
- thermostat for fluent adjustment of temperature with LCD screen
- rollers speed fluent adjustment from panel
- anti-condensation preheating bar before metal rollers (prevents water accumulation on table).
- water tank in the bottom of base-adding water to glue tank by pressing button on panel
- cleaning time after job about 5 minutes
- vacuum table (blower included)
- manual turning-in module
- shelf for paper and boards
- optional rigid boards module for application of glue into stiff surfaces



MADE IN POLAND (EU)

Technical data

| | |
|---|---|
| Range of gluing unit speed (m/min) | 5,6-16 m/min |
| Glue temperature (°C) | 0-95 °C |
| Heating time | approx. 20 minutes |
| Covering material thickness | 80-300 gsm only gluing (up to 5mm with optional rigid boards module) 80-250 gsm turning in |
| Max width of covering material for gluing only (mm) | up to 520 mm(GC480)/800 mm (GC760) |
| Max size of open case | 480 x 820 mm – model GC480 760 x 820 mm – model GC760 (edge turn in 20mm) |
| Min size of open case | 30 x 70 mm |
| Board thickness* | 1 mm-6 mm |
| Spine width | 1-100 mm |
| The minimum distance between boards when producing covers without a spine | from 1 mm |
| Overlap covering material | 8-45 mm |
| Types of covering material | Fabric, laminated paper, photo paper, imitation leather, PVC, polyurethane |
| Maximum no. of boards | 6 when using standard spacers (additional spacers available as an option) |
| Glue application on rigid boards | Up to 5 mm thick with optional kit |
| Glue tank capacity | 4 l |
| Glue types** | Cold water glue or hot animal glue |
| Productivity*** | ~ 150 pcs/hour |
| Dimensions | 1574 x 940 x 1164 mm - GC480 1574 x 1168 x 1164 mm - GC760 |
| Weight | 265 kg (180 kg gluing machine , 85 kg casemaker) - GC480 310 kg (225 kg gluing machine ,85 kg casemaker) - GC760 |
| Power supply | 1-phase, 230 V/50hz ; 2,2 kW |
| Compressed air | not required |
| Vacuum on table | YES (integrated air blower) |

* tested values. Out-of-range materials must be checked prior to purchase

** it is also possible to use cold glue, e.g. in the case

of pasting the inside end paper under a binder

*** depends on the type of material and operator skills



Optional rigid boards module

Sales Office Address

GRAFMASZ
Hennela 10/U14, 02495 Warsaw, POLAND

Factory Address

GRAFMASZ
Kosciuszki 47, 27500 Opatow, POLAND

Grafcut[®]

Phone: +48 22 868 19 86
E-mail: sales@grafcut.eu