

## DBM-700, DBM-700S & DBM-700T

### FEATURES

The DBM-700 Bookletmaker and DBM-700T Trimmer combine to offer high productivity suitable for taking print from multiple presses, whether offset or digital. The DBM-700 has the versatility to take on a wide range of jobs offering printers a choice of finished applications: booklets, corner or side stitched documents. 2 or 4 heavy duty Hohner wire stitching heads, in both flat and loop stitch configurations. The optional DBM-700S adds a square spine to deliver a quality perfect-bound book appearance, while also enabling the system to produce extra thick books of 50 sheets.

- Using Duplo's PC Controller software, the system can easily be managed and controlled by a single operator via a PC.
- Automatic calculation of stitch, fold, fore-edge and head and foot trim positions.
- PC Controller can recall and change between jobs within 60 seconds.
- The DBM-700 system is a modular system and can be customised according to the end users need.
- Clear paper path allows the operator to be in full control of the production process.
- The whole system can be managed by a single operator and requires virtually no operator intervention.

SPECIFICATIONS	
<b>Max Booklet 1-up Production Speed</b>	4600 A5 booklets up to 10 sheets 5200 105mm x 200mm booklets up to 5 sheets
<b>Max Booklet 2-up Production Speed</b>	Up to 9,000 booklets/hr 2-up booklets (when connected with DKTS-200 Trimmer)
<b>Max Booklet Thickness</b>	6mm (30 sheets of 80gsm, 120 page book) 10mm (50 sheets of 80gsm, 200 page book) when using DBM-700S
<b>Flat Sheet Size</b>	Max: W 356mm x L 610mm Min: W 105mm x L 170mm
<b>Finished Untrimmed Booklet Size 1-up Production</b>	Max: W 356mm x L 305mm Min: W 105mm x L 85mm
<b>Finished Booklet Size 1-up Production</b>	Max: W 354mm x L 304mm Min: W 105mm x L 75*mm (needs kit)
<b>Finished Booklet Size 2-up Production</b>	Max: W 171mm x L 254mm (254 is max gutter cut length) 2 Stitches in Each Booklet (Centered) Min: W 114mm x L 75mm 2 Stitches in Each Booklet (Non-Centred) Min: W 105mm x L 75mm (12 pages max) 1 Stitch in Each Booklet Min: W 90mm x L 75mm (12 pages max)
<b>DBM-700T Trimmer Front Knives</b>	1mm to 25mm 85mm standard. With kit up to 75mm with 12 pages or less within 6 mm (max trimming thickness)
<b>Folding Capacity</b>	2 - 30 sheets 50 sheets with DBM-700S
<b>Fine Adjustment</b>	From 0.1mm
<b>Max Stitching Capacity</b>	5mm (50 sheets of 80gsm)
<b>Min/Max Stitching Head Distance (1-up)</b>	60mm - 320mm
<b>Stitching Head Distance (2-up)</b>	58.5mm (55mm is fine adjustment mode)
<b>Stitching Heads</b>	Standard Fitting: 2x Hohner 43/6S 2x2 stitch Optional 4 Hohner Flat/Loop Heads

<b>Controls (DBM-700/700S/700T, DSC10/60i, DSF-2200)</b>	PC Controlled Job Programming, save and recall Automated set-up Microsoft Windows base GUI (Graphical User Interface) Individual control panel for fine adjustment
<b>Job Memories</b>	Infinite from PC Controller
<b>Folding Rollers</b>	Automatic Mechanism
<b>Error Detect Sensors</b>	Paper Feed; Paper Jam, Safety Guards
<b>Features</b>	Quick and automatic job changeover Straight paper path with LED lighting Centre registered system Clear visibility, wide and easy access within each module
<b>DBM-700 Options</b>	DBM-700S Square spine 4 Hohner Flat/Loop Heads DBM-700 Sheet by Sheet Air Kit (multiple sheet feeding)
<b>DBM-700T Options</b>	75mm Trim Kit 50 Sheet Booklet Trim Kit DKT Kicker for LSW
<b>Power Supply</b>	220V - 240V 50/60Hz (DBM-700: 3.5A/DBM-700T:4A) DBM-700 supplies DBM-700S
<b>Power Consumption</b>	DBM-700: 550W DBM-700T: 600W
<b>Dimensions - Net Weights</b>	DBM-700 W 1976mm x D 929mm x H 1507mm 366kg  DBM-700S Square spine W 259mm x D 934mm x H 1140mm 118kg  DBM-700T Trimmer W 719mm x D 1746mm x H 1712mm 241kg  DKTS-200 & LSW2 W 2302mm x D 700mm x H 1169mm 472kg

## CONFIGURATION TABLE

	SHEET FEEDERS		COLLATOR TOWER	BOOKLET MAKER	SQUARE SPINE	TRIMMERS		STACKERS	
	DSF-2200	DSF-6000	DSC-10/60i Collator	DBM-700	DBM-700S	DBM-700T	DKTS-200	DBM-400STR	DC-12JR
<b>DBM-700i Booklet System</b>			Y	Y	Option	Y	Option	Option	Option
<b>DBM-700 Digital Booklet System</b>	Y			Y	Option	Y	Option		
<b>DBM-700 PRO Digital Booklet System</b>		Y		Y	Option	Y	Option		
<b>DBM-700i PRO Duetto Booklet System</b>		Y	Y	Y	Option	Y	Option		

Duplo

# DBM-700

## Booklet Making System



WWW.DUPLOINTERNATIONAL.COM

Duplo International Limited  
Automated Precision House  
Hamm Moor Lane  
Aldstone  
Surrey KT15 2SD

Tel +44(0) 1932 263 900  
Fax +44(0) 1932 263 901  
info@duplointernational.com  
www.duplointernational.com

Duplo is a trade mark of the Duplo Corporation.  
Duplo has a policy of continuous improvement and reserves the right to amend the above specification without prior notice.  
Production rates are based on optimal operating conditions and may vary depending on stock and environmental conditions.



Ref: DBM-700spec/v2/1023

DISCOVER A WORLD OF POSSIBILITIES.

## DSF-2200 SHEET FEEDER

### FEATURES

Duplo's revolutionary DBM-700 & DBM-700T combined with the DSF-2200 Sheet Feeder is the ideal bookletmaking solution for digitally printed sheets. The system is configured to meet the ever-changing demands of today's digital printer and is designed to take printed output from multiple sources.

- Equipped with the Duplo AMS+ (Air Management System Plus) consisting of an 8 belt feeding mechanism which enables the feed head to make contact with a large area of the sheet.
- Both bins come with three separate high-power fans, one to provide suction for feeding, another to provide front air to separate the lead edge of the sheets and a final one to provide side air to separate the sides of the sheets allowing air to flow through the entire length of the sheet for optimal paper separation.
- The operator can easily manage and control the amount of suction, air and separation to accommodate difficult stocks.
- Both bins can be used to feed the cover, contents or sets with self-covers and can feed a variety of paper types and weights up to 300gsm.

SPECIFICATIONS	
<b>Paper Capacity</b>	Main feed tray: 200mm media stack height Auxiliary feed tray: 65mm media stack height
<b>Paper Size</b>	Max W 356mm x L 508mm Max W 230mm x L 610mm Min W 105mm x L 200mm
<b>Paper Weight</b>	From 60gsm to 300gsm
<b>Features</b>	OMR (Optical Mark Reader) end-of-set mark reader, Ultrasonic double sheet detection, Hand feeding, Active anti-static bar & Trail edge air kit (extra air for long sheet sizes up to 610mm in length)

## DSF-6000 SHEET FEEDER

### FEATURES

Duplo's persistent pursuit of the ultimate digital feeding and booklet-making technology culminates in the DBM-700 PRO Digital Booklet System. Configurable with the DBM-700, the DSF-6000 Sheet Feeder offers an unparalleled solution for converting pre-collated digital or offset printed media into high-quality booklets, enabling longer and faster print runs from the latest digital presses.

- Three-sided air separation and integrated static eliminator effectively handle the common static challenges of digitally printed media.
- The multi-function DSF-Twin Feeder can be used as a cover feeder to add a cover and/or an insert to the sets fed from the main tray.
- The standard rolling pallet supplied with the DSF-6000 allows advance loading outside the machine. The pallet loads onto a fork lift inside the feeder and an integral air bed provides easy movement of the paper stack to the correct position.
- An adaptor enables the pallet tray to fit inside a digital press and be loaded automatically. Once full, it is rolled out into the DSF-6000 making the system an ideal solution for finishing production near-line to the press.

SPECIFICATIONS	
<b>AMS+ Feeding System</b>	8 belt suction, top feed from pallet on elevator. Air separation from turbines and pump on 3 sides. Ability to increase the flow and strength of air and vacuum. Side air, trail edge air and front air adjustment.
<b>Paper Capacity</b>	610mm media stack height
<b>Paper Sizes</b>	Max W 364mm x L 525mm Min W 120mm x L 210mm
<b>Paper Weight</b>	From 64gsm to 300gsm
<b>Buffer Capacity</b>	Integrated buffer section with adjustable air separation. 10 sheets or less (1.5mm thickness or less)
<b>Sheet Feed Speed</b>	Up to 600 sheets per minute (A4 SEF)

## DSF-TWIN FEEDER

SPECIFICATIONS	
<b>AMS+ Feeding System</b>	8 belt suction, top feeding. Air separation from turbines and pump on 3 sides. Ability to increase the flow and strength of air and vacuum on each bin. Side air, trail edge air and front air adjustment.
<b>Paper Capacity</b>	2 x 60mm media stack height, top and bottom trays
<b>Paper Sizes</b>	Max W 356mm x L 610mm Min W 120mm x L 210mm
<b>Paper Weight</b>	From 64gsm to 300gsm
<b>Sheet Feed Speed</b>	109 A4 Landscape per minute in sheet feed mode

## DSC-10/60i SUCTION TOWER COLLATOR

### FEATURES

The high speed intelligent DSC-10/60i Suction Collator Towers and the easy to use DBM-700 Bookletmaker and Trimmer provides the operator with the ability to finish booklets of all sizes including A4 landscape.

- Each 10-bin tower comes with AMS+ (Air Management System Plus) as standard.
- Controlled from the PC Controller and the towers, AMS+ manages the high-power fans to create airflow and vacuum independently for each bin, enabling reliable feeding regardless of paper weight or size.
- The DSC-10/60i includes IMBF (Intelligent Multi Bin Feeding) allowing the operator to select each bin individually and feed more than one sheet from one bin.
- Each bin is independent and can be optimised to feed single or multiple sheets, a huge benefit for variable data publications.
- Additional Collating Towers, Straight, Offset or Criss Cross Stacking and Jogging devices can be added at any time.

SPECIFICATIONS	
<b>Bin Capacity</b>	65mm
<b>Paper Size</b>	Max: W 356mm x L 508mm Min: W 105mm x L 148mm Max: W 230mm x L 610mm (max paper size over 508mm in length)
<b>Paper Weight</b>	50gsm - 300gsm from each bin
<b>Max Booklet Processing Speed</b>	Up to 10,000 A5 sets/hr into Jogger or Stacker
<b>Max No of Connectable Towers in Duetto Configuration</b>	Up to 6 x DSC-10/60i Collating Towers
<b>Detection</b>	Miss, Double, Paper Jam and Empty Bin Sensors
<b>Counters</b>	Total, Batch, Set Reject
<b>Controls</b>	PC Controlled Job Programming, save and recall, automated set-up. Microsoft Windows based GUI (Graphical User Interface)

SPECIFICATIONS	
<b>Features</b>	Ultrasonic double sheet detection
<b>Optional Anti-Static Bar</b>	Anti-Static Bar Kit for sheet by sheet mode
<b>Power Supply</b>	Supply from DSF-6000
<b>Dimensions - Net Weights</b>	Stand alone: D 743mm x W 867mm x H 662mm 75kg DSF-6000 and Twin Feeder together: D 797mm x W 1519mm x H 1776mm 377kg

## DKTS-200

### FEATURES

The DKTS-200 is a two-knife trimmer that removes the head and foot of the booklet, working together with a single knife trimmer as part of the DBM-700 Booklet Maker or iSaddle Saddle Stitcher. With optional 6mm and 8mm gutter cutters, five knives enable two-up production of small format booklets, increasing the range of sizes that are possible while also doubling the production speed.

- Servo motors are used throughout for precise movement of the book, ensuring careful handling and minimised risk of scratching sensitive print.
- High-pressure air clears away waste and trim into chutes that lead to a waste bin or optional conveyor.
- The need to lift the heavy gutter cutter unit out of the top of the machine is avoided by incorporating a convenient access door, where the operator needs to simply slide out the assembly.

SPECIFICATIONS	
<b>Minimum Booklet</b>	W 105mm x L 75mm
<b>Maximum Booklet</b>	W 350mm x L 305 mm
<b>Trimming Width</b>	1mm to 30 mm
<b>Trim Thickness</b>	30 sheets (80gsm 3mm)
<b>Processing Speeds</b>	A5 finish 5,050 sets/hr A4 finish 4,000 sets/hr A4 short side finish 3,900 sets/hr A6 finish 4,500 sets/hr
<b>Power Supply</b>	220V - 240V 50Hz/60Hz 3A 383W
<b>Dimensions</b>	D 1367mm x W 2384mm x H 1617mm

SPECIFICATIONS	
<b>Net Weight</b>	598kg
<b>Options</b>	DBM-LSW2/ Belt Stacker  DKT-K Kicker for DKTS-200/ Kicker (Minimum booklet: W 120mm x L 120 mm Maximum booklet: W 350mm x L 250 mm)  DKT-G Gutter Cutter 6mm for DKTS-200/ Gutter Cutter  DKT-G Gutter Cutter 8mm for DKTS-200/ Gutter Cutter

## DBM-400 STR STACKER

SPECIFICATIONS	
<b>Flat Sheet Size</b>	Max W350 x L500mm Min W210 x L139mm
<b>Maximum set thickness</b>	6mm
<b>Stacking methods</b>	Straight or offset
<b>Maximum stack capacity</b>	430mm or 200mm switchable
<b>Processing Speed (based on sets of 10 sheets or less)</b>	Offset 3/600 sets/hour Straight 9,000 sets/hour High speed mode 4,500 sets/hour

## DC-12JR JOGGER

SPECIFICATIONS	
<b>Flat Sheet Size</b>	Max W350 x L500mm Min W200 x L140mm
<b>Stacking methods</b>	Straight
<b>Maximum stack capacity</b>	80 mm
<b>Features</b>	Jogging
<b>Power Supply</b>	220V - 240V 50Hz/60Hz 0.4A